



STEALTH[®] 500

This plant is designed for smaller-sized jobs that require cubicle spec products from a highly portable crushing and screening plant on one chassis.

PRIMARY FEATURES

- 1 Easily transports in one pull. Check with your DOT.
 - » Two-deck inclined screen produces two cubical spec products.
 - » Top-deck retained material is returned to the crusher for further processing.
 - » Hydraulic lift and leveling system enables quick set up and tear down by using the hydraulic run-on legs.
- 2 Totally self-contained, all-electric power. You won't have to worry about hydraulic leaks and failures shutting you down.
 - » Features the industry's only LIFETIME ROTOR WARRANTY on its solid-steel, three-bar, sculptured rotor—the industry's heaviest—to keep you up and crushing.*

* North America only.




ADDITIONAL FEATURES


- » Features closed-circuit crushing and screening on one chassis.
- » Replaces Jaw/Cone/Screen multi-unit systems for a much lower initial investment while maintaining a high production of cubical spec product. Greatly reduces maintenance and fuel costs and is easily transported.
- » Features unique two-step, 5' grizzly deck to remove fines before crushing.
- » Features standard grizzly bypass chute and available cross-belt conveyor with flop gate to allow for either removal of the material that passes through the grizzly deck for stockpiling or blending back with the crushed material.
- » Includes removable electrical control panel featuring pre-wired receptacles for radial stackers.
- » Transports easily with the hydraulic retractable return conveyor.



STEALTH® 500



Solid-steel, three-bar, sculptured rotor with LIFETIME ROTOR WARRANTY, North America only.



Top-deck retained material is returned to the crusher for further processing.

STEALTH® 500 PORTABLE IMPACTOR PLANT TECHNICAL SPECIFICATIONS*

Model	
Impactor	UM-05
Operating Length	63' 0" / 19.2M
Gross Weight	85000 lbs / 38600kg
Travel Length	60' 0" / 18.3M
Travel Width	11' 11" / 3.6M
Travel Height	13' 6" / 4.1M
Feed Hopper Capacity	9yd ³ / 6.9M ³
Feed Hopper Capacity (Tons)	12.2T / 11.1MT
Vibrating Feeder	16' x 32" / 4.9M x 0.8M
Feeder Grizzly Deck	60" long 2 step / 1524mm 2 step
On-Plant Power Supply	150HP / 112 kW all-electric power
Discharge Conveyor Width	36" / 914mm
Two Deck Inclined Screen	4' x 12' / 1.2M x 3.7M
Top Screen Deck Cross Conveyor Width	18" / 457mm
Bottom Screen Deck Cross Conveyor Width	18" / 457mm
Fines Screen Conveyor Width	42" / 1067mm
Return Conveyor (Hydraulic Fold) Width	18" / 457mm

ULTRAMAX® IMPACTOR MODEL AND SPECIFICATIONS*

Model	Diameter x Width		Width x Height		Approx. Weight (lbs / kg)	Rotor Weight (lbs / kg)	Production Capacity**
	Rotor (Inches / Millimeters)	Feed Opening (Inches / Millimeters)	Power Required (HP / kW)				
UM-05	40 x 33 / 1016 x 838	33 x 32 / 838 x 813	75 - 150 / 56 - 112		20900 / 9500	7000 / 3200	Varies by application.

*Design specifications subject to change without notice.

**Contact your Eagle Sales Representative with your specific application for anticipated production capacity.

Call 800-25-EAGLE (800-253-2453) or visit www.EagleCrusher.com
 P.O. Box 537, Galion, OH 44833 • 419-468-2288 • fax: 419-468-4840 • email: sales@eaglecrusher.com

Rev 03/2020

EAGLE CRUSHER®

©2020 Eagle Crusher Company, Inc.